

SETUP SHEET
 FLY-TECH

EVENT			
TRACK			
NAME	DATE		
QUALIFY	FINAL		
BEST LAP	LAP / TIME		/
TEMP. AIR	TEMP. TRACK		

TRACK

SURFACE	☐ ASPHALT	☐ CARPET
LAYOUT	☐ TECHNICAL	☐ MIXED ☐ FAST
TRACTION	☐ LOW	☐ MEDIUM ☐ HIGH

TRANSMISSION

	FRONT	REAR
DIFF OIL	☐ SOLID AXLE	
PULLEY	☐ 38/20T ☐ 40/22T	☐ STD. ☐ LOW FRICTION
PINION	T SPUR	T FDR

SHOCKS

	FRONT	REAR
MEMBRANE	☐ HARD ☐ SOFT ☐ SOFT V2	☐ HARD ☐ SOFT ☐ SOFT V2
SPRINGS		
OIL		
REBOUND (%)		
PISTONS		
LENGTH	mm	mm
STABILIZER	mm	mm

TIRES

	FRONT	REAR
TIRES		
ADDITIVE		
TIMING		
WARMERS	Temp. Timing	Temp. Timing

MOTOR & BATTERIES

MOTOR	TIMING
ESC	BATTERY

WEIGHT BALANCE

WEIGHT	g	BALANCE	FRONT	%	REAR	%
--------	---	---------	-------	---	------	---

BODY

BODY	WING
------	------

BODY POSITION

mm

mm

mm

SIDE PLATE
☐ YES ☐ NO

TOP DECK

☐ 1.6mm ☐ 2.0mm ☐ 1.6mm ☐ 2.0mm

Screws

Shims

TOP DECK CUTTING

COMMENTS

FRONT

CASTER
deg.

BUMP STEER
mm

SHIM
mm

HEIGHT
mm

FF SHIM
mm

RIDE HEIGHT
mm

FR SHIM
mm

SERVO HORN
☐ ALU
☐ STD.

REAR

TOE GAIN
mm

CASTER
deg.

RF SHIM
mm

RIDE HEIGHT
mm

RR SHIM
mm

FRONT

CAMBER
deg.

BODY STOP
☐ YES ☐ NO

SHIM
FF mm
FR mm

SHOCK SHIM
mm

SHIM
mm

FRONT HUB
☐ GRAPHITE
☐ HARD
☐ ALUMINIUM

DROOP
mm
☐ Set with shocks
☐ Set without shocks

BULK BRACE
☐ YES ☐ NO

SHOCK SHIM
mm

SHIM
mm

REAR

CAMBER
deg.

BODY POST
☐ VERTICAL
☐ HORIZONTAL

SHIM
FF mm
FR mm

SHOCK SHIM
mm

SHIM
mm

REAR HUB
☐ GRAPHITE
☐ HARD
☐ ALUMINIUM

DROOP
mm
☐ Set with shocks
☐ Set without shocks

BULK BRACE
☐ YES ☐ NO

SHOCK SHIM
mm

SHIM
mm

TOE
deg.

ACKERMANN
mm

TOE IN
deg.

CENTER WEIGHT
☐ 14g ☐ 10g

DIFF POSITION
☐ UP ☐ DOWN

BEARING HOLDER
☐ 0.75mm
☐ 0.5mm(STD)
☐ 0.25mm

HUB
☐ +0.5mm
☐ STD.
☐ -0.5mm

SHIM
mm

STEER PLATE
☐ 8.5mm
☐ 8.0mm(STD)

SHIM
mm

STEER. LOCK
deg.

FRONT BRACE
☐ YES ☐ NO

MOTOR MOUNT

CHASSIS
☐ GRAPHITE
☐ ALU 2.0mm

FRONT ARMS
☐ HARD
☐ STD.

REAR BRACE
☐ YES ☐ NO

REAR ARMS
☐ HARD
☐ STD.