

F13-III SETUP SHEET

VER.2.0

NAME	
DATE	
TRACK	
EVENT	
TRACTION	
SURFACE	

PINION	TRANSMISSION	SPUR	SHAFT
☐ 18T ☐ 19T ☐ 20T ☐ 19T ☐ 60T ☐ 61T ☐ 62T ☐ 6mm	☐ 23T ☐ 24T ☐ 25T ☐ 2ND ☐ 56T ☐ 57T ☐ 58T ☐ 8mm		
PINION (STD ☐ / HARD ☐)			

FRONT	SHOCKS	REAR
PLA ☐ / AL ☐	SPRING & RETAINER	PLA ☐ / AL ☐
#	OIL	#
☐ STD ☐ OPTION	O-RING	☐ STD ☐ OPTION
☐ STD ☐ OPTION	MEMBRANE	☐ STD ☐ OPTION
PISTON		
HOLE(S) (STD ☐ / SCREW ☐) SHAFT LENGTH		HOLE(S) (STD ☐ / SCREW ☐) SHAFT LENGTH
mm		mm

FRONT	ANTI-ROLL BAR	REAR
mm		mm

FRONT	RIDE HEIGHT	REAR
mm		mm

FRONT	WIDTH	REAR
mm		mm

BRAND	TIRES	CONTROLLED
		☐

LEFT	FRONT	RIGHT	DIAMETER	LEFT	REAR	RIGHT
mm		mm		mm		mm

FRONT	WHEEL PLATE	REAR
☐ YES ☐ NO		☐ YES ☐ NO

BODY

BUMPER WEIGHT & BODY POSITION

WEIGHT ☐ g ☐ g ☐ g

BODY POSITION mm

FRONT CARBON PLATE

☐ CARBON ☐ NO ☐ PLASTIC

REAR BODY MOUNT

☐ PLASTIC (R0373)

SIDE HEIGHT mm

POSITION ☐ 1 ☐ 2

☐ CARBON (R0337)

POSITION (R0337) ☐ 1 ☐ 2 ☐ 3

SPACER mm

POSITION ☐ LOW ☐ HIGH

☐ LIGHT WEIGHT (R0349)

POSITION ☐ 1 ☐ 2

SHOCK TOWER

R0081 R0336

R0081W R0336W

LOWER ARM PLATE

R0355W R0355N R0353

☐ YES ☐ NO

KNUCKLE BASE

SPACER mm

☐ STANDARD (15.5) ☐ R0314B (13.5)

CASTER mm

SPACER mm

TOE ANGLE deg.

SWING SHAFT ☐ 64 ☐ 62 ☐ 60 ☐ 60 (90deg.)

CHASSIS STIFFENER

☐ NO ☐ SCREW ☐ CARBON (R0393) ☐ ALUMINUM (R0417)

SHOCK POSITION

☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

SUSPENSION BUSH

☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

SPACER mm

CAMBER deg.

AXLE SPACER mm

OFFSET SPACER ☐ YES ☐ NO

DOWN STOP mm

TOE ANGLE deg.

HOLDER SUSP BUSH ☐ 20 ☐ 22 ☐ 2 ☐ 1

SWING SHAFT ☐ 54 ☐ 54R (90deg.) ☐ 56

MATERIAL ☐ STANDARD ☐ HARD

MATERIAL ☐ STANDARD ☐ HARD

LOWER ARM PLATE ☐ 0 ☐ 1.5 ☐ 3.0

CENTERING PLATE

☐ STD

mm

☐ REV

mm

SERVO SAVER

STEERING PLATE ☐ 9mm ☐ 10mm ☐ 11mm (STD)

POSITION ☐ FORWARD ☐ MIDDLE ☐ BACKWARD

TIGHTENING mm

SERVO SAVER TYPE ☐ PLASTIC ☐ ALUMINUM (R0259)

SERVO SAVER POSITION ☐ FORWARD ☐ MIDDLE

SPACER mm

SPRING ☐ SOFT ☐ HARD

WEIGHT / CARBON STIFFENER

WEIGHT/CARBON ☐ RIGHT ☐ MIDDLE ☐ LEFT ☐ CARBON

ADDITIONAL WEIGHT g

TOTAL CAR WEIGHT g

☐ CARBON (2P) ☐ STAINLESS (2P) ☐ CARBON (5P) ☐ BRASS (5P)

SHORT WHEEL BASE mm / R - mm

PULLEY STD ☐ / LF ☐ (R0432)

WEIGHT ☐ 15g (T096B) ☐ 10g (SMJ3517 x2) ☐ 7.5g (SMJ3518)

WEIGHT ☐ 15g (T096B) ☐ 10g (SMJ3517 x2) ☐ 7.5g (SMJ3518)

UPPER SUS BUSH ☐ SOFT ☐ HARD

UPPER SUS HOLDER ☐ STANDARD ☐ HARD ☐ ALUMINUM

SIDE SCREW ☐ YES ☐ NO

UPRIGHT UPPER ☐ STANDARD ☐ -1 ☐ 0 ☐ +1

☐ HARD ☐ ALUMINUM

CENTERING (R0328) / OFFSET BUSHING (R0327) ☐ YES ☐ NO

UPRIGHT LOWER ☐ STANDARD ☐ HARD

SUS ARM UPPER ☐ STANDARD ☐ HARD

SUS ARM LOWER ☐ STANDARD ☐ HARD

LOWER ARM END ☐ SOFT ☐ HARD ☐ OLD ☐ NEW

LOWER SUS HOLDER ☐ STANDARD ☐ HARD ☐ ALUMINUM

LOWER SUS BUSH ☐ SOFT ☐ HARD ☐ IN ☐ OUT

ONE WAY ☐ STANDARD ☐ 8mm (R0333) **STOPPER** ☐ YES ☐ NO

SPACER mm

CAMBER deg.

AXLE SPACER mm

OFFSET SPACER ☐ YES ☐ NO

DOWN STOP mm

CHASSIS STIFFENER

☐ NO ☐ SCREW ☐ CARBON (R0393) ☐ ALUMINUM (R0417)

SHOCK POSITION

☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

SUSPENSION BUSH

☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

SPACER mm

CAMBER deg.

AXLE SPACER mm

OFFSET SPACER ☐ YES ☐ NO

DOWN STOP mm

TOE ANGLE deg.

HOLDER SUSP BUSH ☐ 20 ☐ 22 ☐ 2 ☐ 1

SWING SHAFT ☐ 54 ☐ 54R (90deg.) ☐ 56

MATERIAL ☐ STANDARD ☐ HARD

MATERIAL ☐ STANDARD ☐ HARD

LOWER ARM PLATE ☐ 0 ☐ 1.5 ☐ 3.0

CENTERING PLATE

☐ STD

mm

☐ REV

mm

SERVO SAVER

STEERING PLATE ☐ 9mm ☐ 10mm ☐ 11mm (STD)

POSITION ☐ FORWARD ☐ MIDDLE ☐ BACKWARD

TIGHTENING mm

SERVO SAVER TYPE ☐ PLASTIC ☐ ALUMINUM (R0259)

SERVO SAVER POSITION ☐ FORWARD ☐ MIDDLE

SPACER mm

SPRING ☐ SOFT ☐ HARD

WEIGHT / CARBON STIFFENER

WEIGHT/CARBON ☐ RIGHT ☐ MIDDLE ☐ LEFT ☐ CARBON

ADDITIONAL WEIGHT g

TOTAL CAR WEIGHT g

☐ CARBON (2P) ☐ STAINLESS (2P) ☐ CARBON (5P) ☐ BRASS (5P)

SHORT WHEEL BASE mm / R - mm

PULLEY STD ☐ / LF ☐ (R0432)

WEIGHT ☐ 15g (T096B) ☐ 10g (SMJ3517 x2) ☐ 7.5g (SMJ3518)

WEIGHT ☐ 15g (T096B) ☐ 10g (SMJ3517 x2) ☐ 7.5g (SMJ3518)

10254-003 WINNITY F13-3-SETUP SHEET - AR00

UPPER PLATE TYPE

☐ STD

☐ STIFFENER (R0388)

☐ ALUMINUM (R0420)