



SETUP SHEET

Track: _____

Driver: _____

Date: _____

☐ Indoor

☐ Outdoor

☐ Tight / ☐ Open

☐ Slick

☐ Loose Dirt

☐ Blue-Groove

☐ Smooth

☐ Rough

☐ Extra-Rough

FRONT SUSPENSION

(Circle or Check the Appropriate Settings)

☐ In _____°

Toe ☐ Out _____

Ride Height CVD BONES LEVEL

☐ - _____°

Camber ☐ + _____

☐ Stock _____°

Caster ☐ Other _____

☐ No

Sway Bar ☐ Yes size _____

Pivot Support: ☐ 5F(5°), ☐ 7.5F(7.5°), ☐ 10F(10°)

Front Drive:

☐ Diff

☐ One-Way

☐ Plastic

Diff ☐ Steel

of washers under steering/
tie-rod ball studs

Spindle ball stud: _____

Bellcrank ball stud: _____

☐ Standard 42F 42R

☐ Overdrive 41F 42R

☐ Underdrive 42F 41R

☐ Dogbone ☐ Aluminum

☐ CVD ☐ Steel

Drive Shafts

☐ 3

☐ 2

☐ 1

Hole # _____

☐ Outside

☐ Inside

Front S hocks

Oil: _____

Piston: _____ ☐ Standard / ☐ Drilled

Spring: _____

Internal Spring: _____

Limiters: ☐ Inside- _____ ☐ Outside- _____

Notes:

REAR SUSPENSION

Pivot Support: ☐ -IR(-1°), ☐ IR(1°), ☐ 3R(3°)

☐ Inside _____°

Toe-In ☐ Outside _____°

Ride Height CVD BONES JUST ABOVE LEVEL

☐ - _____°

Camber ☐ + _____

☐ Plastic

☐ Dogbone ☐ Aluminum

Diff ☐ Steel

☐ CVD ☐ Steel

☐ Sliders ☐ Plastic

☐ No

Sway Bar ☐ Yes size _____

Rear S hocks

Oil: _____

Piston: _____ ☐ Standard / ☐ Drilled

Spring: _____

Limiters: ☐ Inside _____ ☐ Outside- _____

☐ B ☐ A

Hub Spacing

☐ Forward

☐ Middle

☐ Back

☐ Outside

☐ Inside

Notes:

Tires:

Compound

Foam

Front: _____

Rear: _____

Wing Setup: _____

Motor: _____

Pinion: _____

Spur: _____

Battery Placement: ☐ Back ☐ Forward ☐ Other: _____

Transponder Position: _____

Notes: _____