

Name: _____ Date: _____ Event: _____ Track: _____

Track Conditions

☐ Indoor	☐ Clay	☐ Carpet	☐ Tight	☐ Smooth	☐ Hard Packed	☐ Blue Groove	☐ Wet	Bite: ☐ Low ☐ Med ☐ High
☐ Outdoor	☐ Dirt	☐ Astro	☐ Open	☐ Rough	☐ Loose/Loamy	☐ Dry	☐ Dusty	Tread: ☐ Pin ☐ Ghost ☐ Slicks

Front Suspension

Ride Height	
Camber	
Toe	
Sway Bar	mm

☐ N ☐ W	☐ 2kpi ☐ 4kpi ☐ 6kpi ☐ 8kpi	☐ Composite ☐ Aluminum	☐ Carbon -2mm ☐ Carbon Std ☐ Carbon +2mm
☐ 5 ☐ -2.5 ☐ 0.0 ☐ -2.5 ☐ 5	☐ 1.0 ☐ 0.5 ☐ 0.0	☐ 0.7mm ☐ 1.7mm ☐ 2.7mm	☐ 20° ☐ 22.5° ☐ 25°
		☐ Composite ☐ Aluminum ☐ Brass + g	

Rear Suspension

Ride Height	
Camber	
Sway Bar	mm

☐ Composite ☐ Aluminum ☐ HRC	☐ Carbon -2mm ☐ Carbon Std ☐ Carbon +2mm	☐ X66 ☐ X67 ☐ X68 ☐ X69 ☐ Uni
☐ 4 ☐ 3 ☐ 2 ☐ 1	☐ 4.0 ☐ 4.5 ☐ 5.0 ☐ 5.5 ☐ 6.0	☐ 74 ☐ 75
		☐ 0 ☐ +1 ☐ +2 ☐ +3 ☐ +4

Chassis

Drive Train

Diff Type	☐ Ball Diff ☐ Gear Diff
Setting/Fluid	
Internal Gears	☐ Steel ☐ Composite
Planet Gears	☐ 2 ☐ 4
Slipper	☐ Slipper ☐ Direct Drive

Aerodynamics

Body	
Fr Wing	
Rr Wing	
Wicker	
Angle	
Notes	

Tires

	Front	Rear
Brand		
Tread		
Compound		
Insert		
Sauce		
Wheel		
Notes		

Shocks

	Front	Rear
Oil		
Piston Holes		
Piston	☐ 2mm ☐ 2.5mm	☐ 2mm ☐ 2.5mm
Limiter, Int	mm	mm
Shaft Dia	☐ 3.0mm ☐ 3.5mm	☐ 3.0mm ☐ 3.5mm
Limiter, Ext	mm	mm
Stroke	mm	mm
Eyelet	☐ Std ☐ +2mm	☐ Std ☐ +2mm
Spring		
Spring Cup	☐ Low ☐ Mid ☐ High	☐ Low ☐ Mid ☐ High

Electronics

Radio		ESC	
Servo		Thro Prof	
Battery		Timing Adv	
Battery Wt	g	Initial Brake	
Motor		Drag Brake	
Gearing	/	Thr/Bra EPA	/

☐ 19g ☐ 26g ☐ 37g	☐ +3mm ☐ STD ☐ -3mm	☐ Carbon ☐ Aluminum	☐ Standard ☐ Stiffezel
☐ Carbon ☐ Aluminum ☐ Steel	☐ Standard ☐ Stiffezel	☐ Aluminum ☐ Brass	☐ Carbon
☐ Soft ☐ Standard ☐ Stiffezel	☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5	☐ mm Spacer	☐ mm Spacer
☐ Standard ☐ Stiffezel	☐ mm Spacer	☐ mm Spacer	☐ mm Spacer

Total Weight: _____ g Fr/Rr _____ % / _____ %