SETUP SHEET

XRAY XB2'26

RACE
TRACK
NAME DATE

LAPS | BEST LAP TIME sec
QUALIFYING POSITION | FINAL POSITION

TRACK

SIZE: OPEN MEDIUM TIGHT
TRACTION: VERY-LOW MEDIUM VERY-HIGH
SURFACE: SMOOTH MEDIUM BUMPY
COMPOSITION: CLAY CARPET ASTRO
CONDITION: BLUE GROOVE HARD PACKED DRY / GLUED DUSTY LOAMY WET

TRANSMISSION

BALL DIFF GEAR DIFF ACTIVE DIFF
DIFFERENTIAL OIL cSt 60° 90° 120°
SATELITE GEARS COMPOSITE STEEL GEARS 2 4
SLIPPER mm SOLID AXLE
2-PAD SLIPPER CLUTCH PLATES VENTILATED STANDARD
SLIPPER PADS KIT

GEARING

PINION T SPUR GEAR T

GEAR BOX

TYPE: FRONT LCG 3G 5G REAR 3G LCG KIT
HARDNES: GRAPHITE

SHOCKS

FRONT SHOCKS REAR

SPRINGS
OIL cSt cSt
PISTON
Thickness: 2.5mm 2.0mm KIT Precis.
CAP: ALU KIT Std. -1 -1 | KIT ALU Std. -1 -1
DOWNSTOP SHIM INSERT UNDER PISTON mm mm
LENGTH mm mm
UPSTOP SHIM INSERT ABOVE COLLAR mm mm
COMP. ALU: 0mm -2mm -4mm -6mm
COLLAR
BALL JOINT: +4mm +2mm 0mm | 0mm +2mm +4mm

ANTI ROLL BAR

FRONT /mm THICKNESS REAR /mm

TIRES

FRONT		REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS

MOTOR | ESC
SERVO | BATTERY

BODY

TOTAL WEIGHT

/g

FRONT — APPLIED ● ☑ APPLIED — REAR

CASTER BLOCK: MEDIUM HARD GRAPHITE ALU STEER. ANGLE SCREW
ALU C-HUB: UP /mm DOWN /mm
STEERING BLOCK: MEDIUM HARD GRPHITE ALU
LONGER BUSHINGS: UP DOWN
CAMBER LINK LOCATION
SHIM /mm
LOWER SHOCK POSITION
UPPER SHOCK POSITION: WIDE STD
6 DOT 4 DOT
SHIM /mm
DRIVE SHAFT KIT /mm
SHIM /mm
SHIM /mm
MEDIUM HARD GRAPHITE ALU
REAR UPRIGHT
HIGH LOW X-LOW
LOWER SHOCK POSITION
#325341 ADJ. DRIVE AXLE

ARM MOUNT
0° KIT
0° ALU
-3° ALU
+3° ALU
0° BRASS
TOTAL KICK-UP°
FRONT WING YES NO KIT OTHER
STEERING BUMP STEER
SHIM /mm
ACKERMANN SHIM /mm
CASTER BUSHINGS 0° 2.5° 5°
KICK-UP°
ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP
FRONT
Cutting line +/- from the base line.
+/- mm
Wing length /mm
SHOCK TOWER /mm
Offset wing mounting behind the rear shock tower.
WING TYPE
CENTER FIN YES NO
WING POSITION UP DOWN

FRONT TOE ° OUT
OFFSET
WHEELBASE /mm
ROLL CENTER KIT ALU
STEERING PLATE KIT ALU ARMS KIT ALU
EXTENSION 1 DOT 2 DOTS 3 DOTS
SERVO BRACE YES NO
SERVO POSITION 1 2
BATTERY PLACEMENT
LONG SIDE FRONT
LONG SIDE REAR
REAR TOE ° IN
OFFSET
MOTOR PLATE 1 DOT-KIT
WHEELBASE /mm
BATTERY SIZE STD. SHORT LOW SHORT
SIDE BRACES KIT GRAPHITE
1 2 3 4 5 6 7 8
COOLING FRONT REAR
ROLL CENTER ALU - KIT GRAPHITE COMP.
REAR

REAR
ROLL CENTER SUSPENSION HOLDERS
RF 0.5° 1°
RR 1° 3° 0.5° 1°
SHIM /mm SHIM

FRONT CAMBER /°
GLUING SIDEWALL YES NO
FRONT ARM MEDIUM HARD GRAPHITE
ARM TYPE SHORT - KIT LONG
DIFF HEIGHT /°
RIDE HEIGHT /mm /mm
REAR CAMBER
CUTTING PINS IN OUT NO NO
REAR ARM MEDIUM HARD GRAPHITE
ARM TYPE STANDARD DISENGAGED

LOWER ECCENTRIC SHOCK BALL
FRONT REAR FRONT REAR
ARM MOUNT BALANCE #293085 HUDY Pure Tungsten Weight - 10g.
BALANCE /g BALANCE /g BALANCE /g
3G 5G CHASSIS BRACE
CHASSIS KIT 2.5mm 2.0mm 1.2mm MID-SIZE SHORT EXTRA SHORT
ARM SHIM /mm
SERVO WEIGHT STANDARD LOW PROFILE
FRONT CHASSIS FLEX
ELECTRONICS PLATE NO GRAPHITE WEIGHT
REAR CHASSIS FLEX