NOSRAM

# SETUP - SHEET

# HD TC SPEC - V4.1 / V4.2

| | | | |
|---|---|---|---|
| Driver: | | Motor: | Rotor: mm |
| Date: | | Timing: ° | Gearing: |
| Event: | | Battery: | Charged to: V |
| Track: | | Fan: ☐ ESC | ☐ Motor |
| Racing Class: | Qualify: Finish: | ESC Temp.: blinks | Motor Temp.: blinks |
| Size: | ☐ Small ☐ Medium ☐ Large ☐ Extra Large | Air Temp.: | Track Temp.: |
| Surface: | ☐ Asphalt ☐ Carpet | Car: | |
| Traction: | ☐ Low ☐ Medium ☐ High ☐ Very High | Radio: | |
| Moisture: | ☐ Dry ☐ Damp ☐ Wet | EPA: | % Throttle % Brake |
| Condition: | ☐ Indoor ☐ Outdoor | EXPO: | % Throttle % Brake |

| | MODE | | LED | | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | Brake | Auto Brake (%) | | | | 0 | 3 | 6 | ~~9~~ | 12 | 15 | 20 | 25 | 30 | 35 | 40 |
| 2 | Brake | Brake Type | F | | | SEMI X | X | BDX10 | ~~BDX20~~ | - | | | | | | |
| 3 | Brake | Initial Brake (%) | S | | | ~~0~~ | 3 | 5 | 7 | 9 | 12 | 15 | 18 | 21 | 25 | 30 |
| 4 | Throttle | Initial Drive (%) | | | | - | ~~1~~ | 2 | 3 | 4 | 5 | 7 | 9 | 11 | 13 | 15 |
| 5 | Throttle | Torque Feel | | | | ~~0~~ | 1 | 2 | 3 | 4 | 5 | - | | | | |
| 6 | Throttle | Timing (°) | | | | ~~0~~ | 10 | 15 | 20 | 24 | 28 | 32 | 36 | 40 | 45 | 50 |
| 7 | Throttle | Ramp (°/10kRpm) | | | | ~~0~~ | 5 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| 8 | Throttle | Delay (kRpm) | | F | F | ~~10~~ | 15 | 20 | 25 | 30 | 35 | - | | | | |
| 9 | | Protection | | | | ALL | ~~ESC~~ | NONE | - | | | | | | | |

no value / hidden mode  Factory default settings  F LED blinking fast  S LED blinking slow

| Value Summary: | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|

NOTES


© 2024 **NOSRAM** a brand of Lautenbach Racing Products