NOSRAM POWER - SETUP - SHEET

HD ONROAD - V4.4

Driver:			Motor:	Rotor:	mm
Date:			Timing:	° Gearing:	
Event:			Battery:	Charged to:	V
Track:			Fan: ☐ ESC	☐ Motor	
Racing Class:	Qualify:	Finish:	ESC Temp.:	blinks Motor Temp.:	blinks
Size:	☐ Small ☐ Medium ☐ Large ☐ Extra Large		Air Temp.:	Track Temp.:	
Surface:	☐ Asphalt ☐ Carpet		Car:		
Traction:	☐ Low ☐ Medium ☐ High ☐ Very High		Radio:		
Moisture:	☐ Dry ☐ Damp ☐ Wet		EPA:	% Throttle	% Brake
Condition:	☐ Indoor ☐ Outdoor		EXPO:	% Throttle	% Brake

		MODE	LED	0	1	2	3	4	5	6	7	8	9	10
1	Brake	Auto Brake (%)		0	3	6	~~9~~	11	13	15	17	19	21	23
2	Brake	Brake Type	F	SEMI X	X	~~BDX10~~	BDX20	-						
3	Brake	Initial Brake (%)	S	0	3	5	7	9	~~12~~	15	18	21	25	30
4	Throttle	Initial Drive (%)		-	~~1~~	2	3	4	5	7	9	11	13	15
5	Throttle	Torque Feel		0	1	1.4	1.8	2	2.4	2.8	~~3~~	3.4	3.8	4
6	Power	Timing (°)		0	10	15	~~20~~	24	28	32	36	40	45	50
7	Power	Ramp (°/10kRpm)		3	5	~~7~~	8	9	10	11	12	13	14	15
8	Power	Delay (kRpm)	F F	10	15	~~20~~	25	30	35	-				
9	Power	Trigger Dependency		OFF	1	1.5	2	2.5	3	3.5	~~4~~	4.5	5	6
10	Power	Automatic Turbo	F F F	~~OFF~~	ON	-								
11	Prot.	Protection	F	~~ALL~~	ESC	NONE	-							

hidden modes / no value — Factory default settings — F LED blinking fast — S LED blinking slow

Value Summary:											

NOTES

© 2024 **NOSRAM** a brand of Lautenbach Racing Products GmbH