
LAZER ZX 7.5 Setup Sheet

KYOSHO THE FINEST RADIO CONTROL MODELS

Ver. 1.01 - Arn0

Name | **Date** | **Track / City** | **Event**

Front Suspension




Wheelbase: FR ____ mm
FF ____ mm

Bar end position ____ mm


Sway Bar: ☐ None ☐ ____ mm

Shock Position:



Upper Arm Position:

Shock Stay: ☐ Carbon (Kit) ☐ ____



4.8mm Ball Stud: ☐ UB047 (S:Kit) ☐ UB048 (M) ☐ UB046 (Low:-1mm)

Upper Spacer: ____ mm

Shock Position:

Lower Sus Holder Bush: FF ☐ In ☐ Out ____ FR ☐ In ☐ Out ____

Lower Sus Holder Spacer: FF ____ mm FR ____ mm



Ackerman Spacer: ____ mm


Suspension Arm: ☐ LA429 (Kit) ☐ LAW73B (Carbon Comp)

4.8mm Ball Stud: ☐ UB049 (L: Kit) ☐ UB048 (M)

Upper Spacer: ____ mm

Caster Block: ☐ 7° ☐ 13° ☐ 10° (Kit) ☐ In (Kit) ☐ Out


Camber: ____ °



Axle-Height Spacer: ☐ Up ☐ Down(Kit) ____ mm

Drive Hub: ☐ 4.5mm LAW30GMB(Kit) ☐ 5.2mm UB055-52

Bump Steer Spacer: ____ mm



Toe: ☐ In ☐ Out ____ °

Front Drive


☐ Ball Differential

☐ Steel Gear (Kit : LA402)

☐ Plastic Gear (LAW87)

Oil quantity ____ g

Rear Suspension




Wheelbase: RF ____ mm
RR ____ mm

Bar end position ____ mm

Sway Bar: ☐ None ☐ ____ mm


Shock Position:



Wing Stay:

Upper Arm Position:


Shock Stay: ☐ Carbon (Kit) ☐ ____



4.8mm Ball Stud: ☐ UB047 (S:Kit) ☐ UB048 (M) ☐ UB046 (Low:-1mm)

Upper Spacer: ____ mm

Shock Position:



Sus. Bush:




Suspension Arm: ☐ UB027 (Kit) ☐ UBW009 (Carbon Comp)

Lower Sus Holder Bush:

Toe in: ____ ° RF ☐ In ☐ Out ____ RR ☐ In ☐ Out ____

Lower Sus Holder Spacer: RF ____ mm RR ____ mm

Wheelbase:




____ mm ____ mm

Upper Spacer: ____ mm

Joint Position: ☐ IN (Kit) ☐ OUT

Camber ____ °



Hub. Spacer: ____ mm

Drive Hub: ☐ 4.5mm LAW30GMB (Kit) ☐ 5.2mm UB055-52 ☐ 6.2mm UB055-62

Hub. Bush:



Center Drive

☐ Slipper Clutch (LAW88)

☐ LAW86 Al Diff. Cap

☐ Gear Diff.

Oil quantity ____ g

Rear Drive

☐ Ball Differential


☐ Steel Gear (Kit : LA402)

☐ Plastic Gear (LAW87)

Oil quantity ____ g

Shocks

	Front	Rear
Piston:		
Oil:		
Spring:		
Limiters:	In ____ mm Out ____ mm	In ____ mm Out ____ mm
Length (A):	____ mm	____ mm



O-ring: ☐ ORG03XB (Clear) ☐ ORG03XRB (Red) ☐ ____

Ball End:

	S	M	L
Front:	☐	☐	☐
Rear:	☐	☐	☐

Spring Cup: Front: ☐ Rear: ☐

Chassis

Screw: ☐ Titanium ☐ Steel

Fr ____ mm **- Ride Height -** **Rr** ____ mm



Center Bulk: ☐ Front (Kit) ☐ Rear

Battery Location: ☐ Front (Kit) ☐ Rear

Tyre

	Front	Rear
Tyre:		
Compnd:		
Inserts:		
Wheel:		

Note:

Track Condition

Surface: ☐ Smooth ☐ Sandy ☐ Bumpy


Type: ☐ Astroturf ☐ Carpet ☐ Clay ☐ Dirt ☐ Grass ☐ ____

Condition: ☐ Blue Groove ☐ Hard Packed ☐ Glued ☐ Dry ☐ Damp ☐ Dusty ☐ Wet ☐ High Traction ☐ Med. Traction ☐ Low Traction

Carbon Lower Brace


LAW85

☐ Front



☐ Rear

Front Upper Plate



Electronics

Motor:

Pinion / Spur:

Pinion Gear: ☐ Steel ☐ Alum

Battery:

ESC:

Radio:

Servo:

Body & Wing

Body:

Wing:

Wing Hole Position: ____ mm

Wing Dam Height: ____ mm

Lip Height: ____ mm

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

Cut Line

