



Driver Chris `Doughty ☐ Indoor ☐ Slick ☐ Smooth
Date July 2003 ☒ Outdoor ☐ Loose Dirt ☐ Rough
Track Batley Grass ☒ Tight ☐ Open ☐ Blue Groove ☐ Extra Rough

Front Suspension

Toe In ☐ 0 °
Toe Out ☐ 0 °

Pivot Support ☐ 5F(5°), ☒ 7.5F(7.5°) ☐ 10F(10°)

☒ Standard 42F 42R
☐ Overdrive 41F 41R
☐ Underdrive 42F 41R

Ride Height Level set to Rear Setting

Camber ☒ - ☐ + 1 °

Caster ☒ Stock ☐ Other _____ °

Sway Bar ☒ No ☐ Yes size _____

Front Drive:

☐ Diff
☒ One-Way
☒ Plastic Diff
☐ Steel Diff

Drive Shafts ☐ Dogbone ☐ Aluminium
☒ CVD ☒ Steel

Number of washers
0

Number of washers under steering / tie rod ball studs

Spindle ball stud: 0

Bellcrank ball stud: 0

Hole # 1

☐ Outside ☒ Inside

Front Shocks

Oil: 50

Piston: Orange ☐ Standard ☐ Drilled

Spring: Black

Internal Spring: yes

Limiters: Inside 1.5mm ☐ Outside 0

Notes _____

REAR SUSPENSION

Inside ☒ 3 °
Toe In Outside ☐

Ride Height Driveshaft level

Camber ☒ - ☐ + 1 °

Diff
☒ Plastic
☐ Steel

Sway Bar
☒ No ☐ Yes size _____

Drive Shafts

☒ Dogbone ☒ Aluminium
☐ CVD ☐ Steel
☐ Sliders ☐ Plastic

Pivot Support: ☐ -IR(-1°), ☒ IR(1°), ☐ 3R(3°).

Hub Spacing
☐ Forward
☐ Middle
☒ Back

☐ Outside ☒ Inside

Rear Shocks

Oil: 20

Piston: RED ☐ Standard ☐ Drilled

Spring: RED

Limiters: Inside 5mm ☐ Outside 0

Notes _____

Tyres _____ Compound _____ Foam _____
Front _____
Rear _____
Wing setup low
Battery Placement ☐ Back ☒ Forward ☐ Other _____
Transponder Position _____
Motor 9 x 2 Pinion 19 Spur 90

Notes _____