Art. SS20120925 01
Be Pro, be easy! New setting up method of our new firmware.

TIMING SYSTEM
TURBO TIMING SYSTEM
BRAKING SYSTEM
New setting up method of our new firmware.

VRITRA brushless system
ORCA®

SETUP SHEET

ESC MODE ● *Modified*

FIRMWARE VERSION ● *3.3*

DATE ● *19.01.2014*

TRACK ● *EOS Berlin*

TRACTION ● (●) HIGH ( ) MID ( ) LOW

MOTOR ● *6.5T RX2* ENDBELL ● *std*

FINAL GEAR RATIO ●

AIR TEMP. ● *23°C* GROUND TEMP. ● *23°C*

ESC TEMP. ● *50°C* MOTOR TEMP. ● *55°C*

REMARK ●

Editable by Arn

MODIFY MODE | STOCK MODE

TIMING SYSTEM

1. TIMING START:
Blinky 5° 10° [✓15°] 20° 25° 30° 35° 40°

2. TIMING: MODIFY MODE
OFF 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
[✓16] 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31
32 33 34 35 36 37 38 39 40 STOCK MODE

3. TIMING INTERVAL:
-3 -2 -1 NORMAL +1 [✓+2] +3

TURBO TIMING SYSTEM

4. TURBO DELAY:
0.02's 0.03's [✓0.04's] 0.05's 0.06's 0.07's 0.08's 0.09's 0.10's 0.11's 0.12's 0.13's 0.14's 0.15's

5. TURBO TIMING: MODIFY MODE
OFF 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
16 17 18 19 20 21 22 23 24 [✓25] 26 27 28 29 30 31
32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47
48 49 50 51 52 53 54 55 56 57 58 59 60 STOCK MODE

6. TURBO INTERVAL:
-6 -5 -4 -3 -2 -1 NORMAL +1 +2 [✓+3] +4 +5 +6

BRAKING SYSTEM

7. DRAG BRAKE:
OFF 1% 2% 3% 4% 5% 6% 7% 8% 9% 10% 11% 12% 13% [✓14%] 15%
16% 17% 18% 19% 20% 21% 22% 23% 24% 25%

8. INITIAL BRAKE:
OFF 1% 2% [✓3%] 4% 5% 6% 7% 8% 9% 10% 11% 12% 13% 14% 15%
16% 17% 18% 19% 20% 21% 22% 23% 24% 25% 26% 27% 28% 29% 30%

9. BRAKE FREQ: 1K [✓2K] 4K

DRIVE FEEL

10. PUNCH
LV1 LV2 LV3 LV4 LV5 LV6 LV7 [✓LV8] LV9 LV10

11. PWM
2K 4K [✓8K] 32K

12. SAVE PARAMETER 1 2

Copyright @2012 ORCA®. All right reserved. Images may not be used without premission.
www.orcarc.com