Art. SS20120925

01

Be Pro, be easy!
New setting up method of our new firmware.

TIMING SYSTEM
TURBO TIMING SYSTEM
BRAKING SYSTEM
New setting up method of our new firmware.

VRITRA brushless system
ORCA®

SETUP SHEET

ESC MODE	Modified
FIRMWARE VERSION	VX 3.00 1209220
DATE	2012.12.09
TRACK	RC Landia, Scandiano
TRACTION	○ HIGH ● MID ○ LOW
MOTOR	RX 4.5T
ENDBELL	0
FINAL GEAR RATIO	8.7:1
AIR TEMP.	15°C
GROUND TEMP.	°C
ESC TEMP.	50°C
MOTOR TEMP.	65°C
REMARK	

Editable by Arn0 at PetitRC.com

MODIFY MODE | STOCK MODE

TIMING SYSTEM

1. TIMING START:

Blinky	5°	10°	15°	20°	25°	30°	35° ✓	40°

2. TIMING: MODIFY MODE

OFF	1	2	3	4	5	6	7 ✓	8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
32	33	34	35	36	37	38	39	40	STOCK MODE						

3. TIMING INTERVAL:

-3	-2	-1	NORMAL	+1	+2	+3 ✓

TURBO TIMING SYSTEM

4. TURBO DELAY:

0.02's	0.03's	0.04's	0.05's	0.06's	0.07's	0.08's	0.09's	0.10's	0.11s	0.12's	0.13's	0.14's	0.15's

5. TURBO TIMING: MODIFY MODE

OFF	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23	24	25 ✓	26	27	28	29	30	31
32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55	56	57	58	59	60	STOCK MODE		

6. TURBO INTERVAL:

-6	-5	-4	-3	-2	-1	NORMAL	+1	+2	+3 ✓	+4	+5	+6

BRAKING SYSTEM

7. DRAG BRAKE:

OFF	1%	2%	3%	4%	5% ✓	6%	7%	8%	9%	10%	11%	12%	13%	14%	15%
16%	17%	18%	19%	20%	21%	22%	23%	24%	25%						

8. INITIAL BRAKE:

OFF ✓	1%	2%	3%	4%	5%	6%	7%	8%	9%	10%	11%	12%	13%	14%	15%
16%	17%	18%	19%	20%	21%	22%	23%	24%	25%	26%	27%	28%	29%	30%	

9. BRAKE FREQ:

1K	2K ✓	4K

10. PUNCH

LV1	LV2	LV3	LV4 ✓	LV5	LV6	LV7	LV8	LV9	LV10

11. PWM

2K	4K	8K	32K ✓

12. SAVE PARAMETER 1 ✓ 2

DRIVE FEEL

Copyright © 2012 ORCA®. All rights reserved. Images may not be used without premission.

www.orcarc.com