BLACKBOX 410R
ELECTRONICS SET-UP SHEET

Voltage input:	3.7 - 7.4/ 1-2 LiPo
On resistance (Ω)	0.00035 x2
Continuous current (A)	150
Weight without wires (g)	49
Motor limit (2-pole/4-pole)	3.5T/4800kV
SBEC	5.5 - 7.0V/5A

DRIVER: Brent Thielke **EVENT:** Club Race **TRACK:** OCRC Raceway **DATE:** 8/7/14

VEHICLE: AE B5M **CONDITIONS:** Med/high grip, indoor **BATTERY:** Reedy #738 **TEMP:** 80F

ESC INFO

FIRMWARE:	2.7
CAPACITOR TYPE:	Reedy heavy-duty
FAN (YES/NO):	No
WIRE SIZE:	14
PROFILE #:	1

BRAKE

DRAG BRAKE:	12
BRAKE FREQ:	1000
BRAKE STRENGTH:	85
BRAKE CURVE:	-10

SPD SENS BRAKE

LOW SPEED STR:	12
HIGH SPEED STR:	12
SWITCHOVER RPM:	Disable

THROTTLE

THROTTLE FREQ:	12000
THROTTLE PUNCH:	100
THROTTLE CURVE:	0
DEAD BAND:	8

MOTOR POWER

ACCEL BOOST

START RPM:	Disable
FINISH RPM:	Disable
MAX ADV TIMING:	0

TOP SPEED TIMING

SLEW RATE:	5/0.1
MAX ADV TIMING:	0
DELAY TIME:	0

MISC CONTROL

RUN MODE:	Race Open
MOTOR TYPE:	2-pole
SBEC VOLTAGE:	5.5
FORWARD POWER:	100
REVERSE POWER:	25

PROTECTION

BATTERY CUTOFF:	6.0
ESC TEMP CUTOFF:	230

MOTOR SETTINGS

MOTOR:	Reedy Sonic 540 Mach 2
WIND:	8.0
TIMING:	15
ROTOR:	12.5 x 25 #958
FDR/ROLLOUT:	22/78
TEMPERATURE:	N/A

RADIO SETTINGS

THROTTLE EPA:	100
BRAKE EPA:	85
THROTTLE EXPO:	0
BRAKE EXPO:	0

NOTES:

REEDY POWERED
www.ReedyPower.com

www.facebook.com/ReedyPower

twitter.com/ReedyPower

IFMAR WORLD CHAMPIONS 29 TIME REEDY