

Driver Name : *Viktor Wilck*

Firmware Version : Date : *Feb 2020*

Track : *RC Addict* Track Temp:

Traction : *Medium* Motor : *Dash 4.5t V2* Rotor :

Endbell : *30* Final Gear Ratio : *7.4*

After Run

ESC Temp : *130* Motor Temp : *110*

Remark :

Quick Setup	Range	Blinky	Modified	Open Stock	Off Road
Softening	Level 1-5		*1*		
Punch	Level 1-15		*2*		
PWM	2000-32000Hz		*8000*		
Boost	Off-100		*2*		
Turbo	Off-100		*60*		
Turbo Up Rate	5 4 3 2 1 Normal -1 -2 -3 -4 -5		*Normal*		
Turbo Down Rate	5 4 3 2 1 Normal -1 -2 -3 -4 -5		*-20*		
Compress	0%-50%		*2%*		
Drag Brake	Off-30%		*15*		
Advanced Setup	**Range**	**Blinky**	**Modified**	**Open Stock**	**Off Road**
PWM	2000-32000Hz				
Compress	0-50%				
Boost Start	0-90%		*50*		
Boost Range	0-50%		*45*		
Turbo Delay	0ff-0.10s		*0.02*		
Turbo Start	40-100%		*92%*		
Brake Frequency	500-5000Hz		*1100*		
Initial Brake	0-60%		*32*		
Brake Range	0-100%		*32*		
Max Brake Force	0-100%		*80%*		
Initial Setup	**Range**	**Blinky**	**Modified**	**Open Stock**	**Off Road**
Running Mode	Forward/Brake Forward/Reverse Forward/Brake/Reverse Forward/Hold/Reverse		*F/B*		
Reverse Force	0-100%		*0%*		
Battery Type	LiPolymer FI-FE NiXX		*LIPO*		
Cutoff Voltage	Off Low Middle High		*OFF*		
ESC Heat Protection	95 105 120 No Protection		*OFF*		
Motor Heat Protection	95 105 120 No Protection		*OFF*		
Neutral Range	2%-15%		*6%*		
BEC Voltage	6v 7v		*7%*		
Motor Direction	CCW CW		*CCW*		