LAZER ZX6 SET UP SHEET

KYOSHO® THE FINEST RADIO CONTROL MODELS

Name	Date	Track / City	Event
Remy BERTRAND	14/09/14	Bonneville	French nationals rd5

Front Suspension:

Shock Position: ① ③

Upper Arm Position: ① ③

4.8mm Ball Stud:
- [x] 97050M(Std)
- [ ] UM129

Upper Spacer: 0 mm

Camber 1,5 ° (- / +)

Spacer: 1 mm

Shock Position: ① ③

Bump Steer Spacer: 0 mm

Toe:
- [ ] In
- [x] Out 1 °

Sway Bar:
- [x] None
- [ ] ____ mm

Axle-Height Spacer:
- [ ] Up
- [x] Down

Caster Block:
- [ ] 7°
- [x] 10°

Ackerman Spacer: 0 mm

Lower Sus Holder Block:
Front B in Rear B in

Lower Sus Holder Spacer:
Front 0.5 mm Rear 0.5 mm

Wheelbase:
Front 1 mm
Rear 0 mm

Comments:

Front Diff:
- [ ] Gear Diff. #
- [x] Ball Diff. loose

Rear Suspension:

Shock Position: ① ③ ④

Wing Stay Position: ① ③

Upper Arm Position: ② ③

4.8mm Ball Stud:
- [x] 97050M(Std)
- [ ] UM129

Upper Spacer: 1 mm

Sus. Arm:
- [x] LA272(Std)
- [ ] UM713

Camber 2° (- / +)

Shock Position: ②

UM713 ① ② ③

Hub Carrier: ①
- [ ] Type-B (UM519)
- [ ] Type-B2 (UM519-2)
- [ ] 0°Type-B(UM519)
- [ ] 0°Type-B2(UM519-2)
- [x] 0°Alu(UMW704-0)
- [ ] 0.5°Alu(UMW704-05)
- [ ] 1°Alu(UMW704-1)

③ ④

Upper Spacer: 2 mm

Sway Bar:
- [ ] None
- [x] 1.2 mm

Lower Sus Holder Block:
Front D in Rear D out

Toe In: ____ °

Lower Sus Holder Spacer:
Front 1 mm Rear 0.5 mm

Wheelbase:
Front: 1 mm
Rear: 1 mm

Comments:

Slipper Type:
- [ ] Separates
- [ ] Direct

Rear Diff:
- [ ] Gear Diff. #
- [x] Ball Diff. loose

Shock:

	Front	Rear
Shock Piston:	2x1.6	2x1.6
Shock Oil:	# Losi 35	# Losi 27.5
Shock Spring:	Red	Gold
Limiters:	in ____ mm / out ____ mm	in ____ mm / out ____ mm
Shock Length(A):	____ mm	____ mm

A

Shock Top Type: [x] Alu(UM719/Std) [ ] UM753-1

5.8mm Ball End:

	S	M	L
Front:	[ ]	[x]	[ ]
Rear:	[x]	[ ]	[ ]

Chassis:

Ride Height:

A B

Front 22 mm

Rear [x] A [ ] B 22 mm

Tire:

	Front	Rear
Tire:	Sweep SQ blue	Sweep SQ blue
Inserts:	sweep insert	sweep insert
Wheel:	Kit	Kit
Traction Compound:		

Electronics:

Battery: [ ] Saddle [x] Short

Motor Position: [ ] Front [x] Rear

Servo Mounting: [ ] Straight [x] Sideways

Motor: Orion 6.5 T

Motor Timing: ____

Pinion/Spur: 19/78

ESC: ____

Setting: ____

Radio: ____

Servo: shorty

Body / Wing:

Body: Kit

Wing: Kit

Wing Mount: [ ] Narrow [x] Wide

Wing Angle: [ ] 4° [x] 7° [ ] 10°

Wing Dum Height: ____ mm

Lip Height: ____ mm

Material:

Screw: [x] Steel [ ] Titanium

Pinion Gear: [x] Steel [ ] Aluminium

Shock O-Ring: [ ] O-ring [x] X-ring [x] Red [ ] Clear

Comment :

Editable by Arn0 at PetitRC.com

No added weight.
Servo + receiver + transponder on the motor side, in front.

- [ ] Smooth
- [x] Bumpy
- [x] Low Traction
- [ ] Med.Traction
- [ ] High Traction
- [ ] Wet
- [x] Dry
- [ ] Sandy
- [ ] Soft Dirt
- [ ] Grass
- [ ] BlueGroove
- [ ] Clay
- [ ] Dusty
- [ ] ____

Arn0 v1.0