2WDRC.com
4WDRC.com

X-6² Setup Sheet

X-FACTORY R/C
XFactoryRC.com

Driver: *Dan Griffin*															Date:				
Track / Location: *CRCRC*															Event:				
Tight	Both	Open		Wet	Damp	Dry		Smooth				Rough			Slippery	Medium		High-Bite	
□	□	□		□	□	***X***		***X***	□	□	□	□			***X***	□	□	□	□

FRONT

SUSPENSION

Ride Height: *24-25* mm

Camber: _____° Toe: _____° □In/ □Out

Camber Link: inside: *1* (1=inside) Washers: *2* Outside: *A* (A=inside)

Caster Block: □20° □25°(Stock) ***X***30°
□Back ***X***Forward (Stock)

Bump steer spacers: □.050" (Stock)/ □OTHER: *0,060*
Spacers under outer tie-rod ballstud: _____

Axle: □Trailing (Stock) / ***X***Inline

Axle height: □Top □Middle ***X***Bottom

Steering Ackerman: ***X***Forward (Stock) □Back

Servo Position: *Forward*

SHOCKS

□Associated / ***X***Losi

Mounting (T/B): *2* / *Outside* (1=inside)

Spring: *Orange*

Piston: *56 (Red)*
XStandard/ □Drilled

Oil: *30-32.5wt*

Limiting (T/B): 0.090 / _____

REAR

SUSPENSION

Transmission: ***X***4 Gear (Stock) / □3 Gear

Transmission Height: ***X***.060 (Stock) / □Other: _____

Ride Height: *22-25* mm

Camber: _____ ° Toe Bar: □3° / ***X***4° Anti-squat: *3°*
Extra Hub Toe In/Out: _____

Rear Roll Bar: _____

Camber Link: Inside: *2* (1=inside) Washers: *0* Outside: *B* (A=inside)

Hub spacing: □Forward □Middle ***X***Back
Arm spacing: □Forward □Middle ***X***Back

SHOCKS

□Associated / ***X***Losi

Mounting (T/B): *1* / *Middle* (1=inside)

Spring: *Pink*

Piston: *57 (Grey)*
XStandard/ □Drilled

Oil: *22.5wt*

Limiting (T/B): _____/_____

OTHER

no weight in front end, 1/2 oz weight near motor

hubs forward, arms as far forward as you can put them (about .020 back from full forward)
I run the DDP brace when track is higher bite and remove it when the track starts getting loose.

Front tires:	Front inserts:	
Rear tires:	Rear inserts:	
ESC:	Motor:	
Battery:		Pinion/spur: ____/ *75*
Wing:		

PetitRC.com