X – 6 Set-Up Sheet

Driver:	Date:

Track: General Low Bite Set Up

□ Tight / □ Open	□ Wet / ■ Dry	□ Smooth / ■ Rough	Slippery □ ■ □ □ □ High-Bite

Front

Suspension

Ride Height: ____Arms Below Level_____

Camber: _-1__ ° Toe: __1__ ° ■ In / □ Out

Camber Link: Inside: __1__ (1=inside) Washers: __2__ Outside: __A__ (A=inside)

Caster Block: □ 20° □ 25° (stock) ■ 30°

□ Back ■ Forward (stock)

Bump Steer Spacers: ■ .050" (Stock) / □ Other: _____
(Spacers under outer Tie-Rod Ballstud)

Axle: ■ Trailing (stock) / □ Inline

Axle Height: □ Top ■ Middle □ Bottom

Steering Ackerman: □ Forward (stock) ■ Back

Shocks

□ Associated / ■ Losi

Mounting (T/B): _3__/__2__ (1=inside)

Spring:___Orange_____

Piston: __56_ ■ Std / □ Drilled

Oil: ____25_____

Limiting (T/B): _.030"_/__0_

Rear

Suspension

Transmission Height: □ .060 (stock) □ Other: __.090"__

Ride Height: ____CVD's above level_____

Camber: __-1.5_ ° Toe Bar: □ 3° ■ 4° Antisquat: _.060"_

Camber Link: Inside: __1__ (1=inside) Washers: __1__ Outside: __A__ (A=inside)

Hub Spacing: ■ Forward □ Middle □ Back

Arm Spacing: ■ Forward □ Middle □ Back

Shocks

□ Associated / ■ Losi

Mounting (T/B): __2_/_2__ (1=inside)

Spring:__Pink_____

Piston: _55__ ■ Std / □ Drilled

Oil: ___30_____

Limiting (T/B): __0_/_0__

Other

Notes:__1/2 oz of weight in the rear, add another ½ oz if desired_____

Front Tire:

Rear Tire:

Motor: 13x2	Pinion/Spur: __22_/_78__

Wing: 1st cutline down; full side dams