SET-UP SHEET

XB2'26 Willspeed FastFox

WS XRAY XB2'26

RACE	1066 Club Night
TRACK	
NAME	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	1st	FINAL POSITION	1st

TRACK

SIZE	☒ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ ☐ ☐ ☐ ☐ ☐ ☒ ☐ ☐		
	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☒ CARPET	☐ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☒ DRY
☐ GLUED	☐ DUSTY	☐ LOAMY	☐ WET

TRANSMISSION

BALL DIFF ☐ GEAR DIFF ☒ ACTIVE DIFF ☐

DIFFERENTIAL OIL 30k cSt — 60° 90° 120°

SATELITE GEARS COMPOSITE ☐ ☐ STEEL GEARS 2 ☐ ☒ 4

SLIPPER ____ mm SOLID AXLE ☐

2-PAD SLIPPER CLUTCH PLATES SLIPPER PADS

VENTILATED ☐ ☐ STANDARD KIT ☒

GEARING

PINION	T	SPUR GEAR	T

GEAR BOX

TYPE		HARDNESS	
FRONT LCG 3G	☒	☐ 5G	☐
REAR 3G LCG	☐	KIT	☒ ☐ GRAPHITE

SHOCKS

FRONT	SHOCKS	REAR
WS Green	SPRINGS	WS Green
cSt 450	OIL	400 cSt
2 HOLES ☒	☒ ø1.6mm ☐ ☐ ø1.8mm ☒	2 HOLES ☒
HOLES	ø mm ø mm	HOLES
KIT ☒ ALU ☐	CAP ALU ☒ KIT ☐	
Previous 0 -1 -1		Previous 0 -1 -1
Piston 2.0 ☐ ☒ 2.5		Piston 2.5 ☒ ☐ 2.0
KIT ☒ ☐ Precis.		Precis. ☐ ☒ KIT
Downstop shim 0 mm		mm 0 Downstop shim
Length 21 mm		mm 21.5 Length
Upstop shim 0 mm		mm 0 Upstop shim
WS ☒ COMP. ☐ ALU ☐	0mm ☐ -2mm ☐ -4mm ☐ -6mm ☐ COLLAR	0mm ☐ -2mm ☐ -4mm ☐ -6mm ☐ WS ☒ COMP. ☐ ALU ☐
☐ ☐ ☒ +4mm +2mm 0mm	BALL JOINT	0mm ☐ +2mm ☒ +4mm ☐

ANTI ROLL BAR

FRONT		REAR
1.2 /mm	THICKNESS	1.4 /mm

TIRES

FRONT	TIRES	REAR
SCH	BRAND	SCH
Y	COMPOUND	Y
N/A	INSERTS	Cragg
JC	WHEELS	JC

ELECTRONICS

MOTOR			SPEEDO
SERVO			BATTERY

BODY

☐ LIGHT

TOTAL WEIGHT

/g

COMMENT

WS 0 Stainless Bulkhead
Note shims behind push rods used for outside hole on arm

FRONT (APPLIED ◉ ☒ APPLIED) REAR

LONGER BUSHINGS UP ☐ DOWN ☒

CASTER BLOCK: MEDIUM ☐ HARD ☐ GRAPHITE ☒ ALU ☐ STEER. ANGLE SCREW ☐

ALU C-HUB: UP /mm DOWN /mm

CAMBER LINK LOCATION 2 1

LOWER LINK POSITION 2 1

STEERING BLOCK: MEDIUM ☐ GRAPHITE ☒ HARD ☐ ALU ☐

SHIM 2 /mm

SHIM 0 /mm

DRIVE SHAFT ☒ KIT /mm

☒ GRAPHITE ☐ MED ☐ ALU ☐ HARD

SHIM 2 /mm

REAR UPRIGHT ☐ HIGH ☒ LOW

SHIM 3 /mm

LOWER LINK POSITION 1 2 3

1 2 3 4 #325341 ADJ. DRIVE AXLE

ARM MOUNT 0° ☐ KIT 0° ☐ ALU -3° ☐ ALU +3° ☐ ALU 0° ☐ BRASS +3° ☐ WS Steel 0° ☒ WS Steel

FRONT WING YES ☐ ☒ NO KIT ☐ ☐ OTHER

ACKERMANN SHIM 1 /mm

STEERING BUMP STEER SHIM 1 /mm

Cutting line +/− from the base line. +/- mm Wing length /mm WING MOUNT /mm

Offset wing mounting behind the rear wing mount.

CENTER FIN YES ☐ ☒ NO

WING TYPE

TOTAL KICK-UP° 24.5 (ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP) KICK-UP

CASTER BUSHINGS 0° ☐ 2.5° ☒ 5° ☐

ROCKER	TOP SHOCK	LOWER SHOCK	LOWER SHOCK	TOP SHOCK	ROCKER	WING POSITION
Front ☐	Top ☐	Front ☐	Forward ☐ ☐ ☒	Top ☐	Front ☐	UP ☐
Middle ☒	Middle ☒	Middle ☒	Backward ☐ ☐ ☐	Middle ☒	Middle ☒	DOWN ☒
Back ☐	Bottom ☐	Back ☐	1 2 3 4 5 6	Bottom ☐	Back ☐	

FRONT TOE 0 ° OUT

OFFSET 1.5

WHEELBASE 0 /mm

ROLL CENTER KIT ☒ ALU ☐

STEERING: PLATE KIT ☒ ALU ☐ ARMS KIT ☐ ALU ☐

SHIM 2 /mm

EXTENSION 1 DOT ☐ 2 DOTS ☒ 3 DOTS ☐

SERVO BRACE YES ☒ ☐ NO

SERVO POSITION 1 2

REAR TOE 2 ° IN

BATTERY PLACEMENT LONG SIDE FRONT ☐ LONG SIDE REAR ☒

MOTOR PLATE 1 DOT-KIT ☒

OFFSET 2.25

WHEELBASE 2 /mm

BATTERY SIZE ☐ STD. SHORT ☒ LOW SHORT

ROLL CENTER ALU - KIT ☒ GRAPHITE ☐ COMP. ☐

SHIM 1 /mm 2 /mm

COOLING FRONT ☐ ☐ REAR

1 2 3 4 5 6 7 8

REAR ROLL CENTER SUSPENSION HOLDERS

RF 0.5° ☐ ☒ 1°

RR 0.5° ☐ ☐ 1° XRAY 3° 3° 1°

RR 0.5° ☐ ☒ 1° XRAY 1°

SHIM 0 /mm SHIM

FRONT CAMBER 1.5 /°

GLUING SIDEWALL YES ☐ ☒ NO

FRONT ARM: MEDIUM ☐ HARD ☐ GRAPHITE ☒

ARM TYPE: SHORT - KIT ☒ LONG ☐

DIFF HEIGHT

RIDE HEIGHT 14 /mm

RIDE HEIGHT #107763 GAUGE

14 /mm RIDE HEIGHT

1.5 /° REAR CAMBER

CUTTING PINS IN ☐ ☐ OUT NO ☒ ☒ NO

REAR ARM: MEDIUM ☐ HARD ☐ GRAPHITE ☒

ARM TYPE: STANDARD ☒ DISENGAGED ☐

LOWER ECCENTRIC SHOCK BALL

FRONT ☐ ☐ REAR FRONT ☐ ☐ REAR

ARM MOUNT BALANCE #293085 HUDY Pure Tungsten Weight - 10g. /g

BALANCE /g BALANCE /g BALANCE /g

4 3 2 1 3G ☒ CHASSIS BRACE 5G ☐ 3 2 1

SERVO WEIGHT: STANDARD ☐ LOW PROFILE ☒

ELECTRONICS PLATE: NO ☐ GRAPHITE ☒ WEIGHT ☐

ARM SHIM 0 /mm